

FOR PROFESSIONAL USE ONLY

DIRECTIONS FOR USE: FIREFOG 404 is ready to use; do not dilute. **MUST BE USED IN AN APPROVED THERMAL FOGGER.** Fog 1 or 2 ounces of FIREFOG 404 per 1000 cubic feet of space to be treated. Adjust the fog rate and moistness as instructed by the thermal fogger manufacturer. Normally in thermal fogging when the space is filled with a medium dense fog the space has been properly treated.

IMPORTANT: Since the petroleum distillates in all thermal fogging products are combustible, all open flames, pilots, smoking and other sources of sparks and ignition should be turned off prior to fogging. **REFER TO MANUFACTURER'S SAFETY BULLETIN IF UNFAMILIAR WITH SAFETY PROCEDURES.** No people or pets should occupy the area during the treatment until after the space has been properly ventilated.

During and after fogging the fog needs to be retained in the space as long as practical. Keep doors and windows closed for a minimum of 15 minutes after application. Before reoccupying, the space must be thoroughly ventilated. Allow fresh air to enter by opening doors and windows and when possible use an Airmover or exhaust fan to achieve at least one exchange of air.

FIREFOG 404

Thermal Fogging Compound

CONTROL OF ORGANIC ODORS
Fire & Smoke - Tobacco - Garbage
Skunk - Dead Body - Locker Rooms

Net Contents: 1 Gallon (3.78 Liters)

CAUTION: Keep Out of Reach of Children
See side panel for additional precautions

FIREFOG 404 employs the latest chemical technology to effectively neutralize smoke odors and a variety of organic malodors. FIREFOG 404 works with a combination of multi-phase odor counteractants and lightly scented air fresheners. FIREFOG 404 does not rely on sweet or heavy masking smells but does impart a pleasant lasting Fresh-N-Clean fragrance. No heavy, oily odor. A special petroleum based smoke odor and malodor control formula for use in the gas and electric hot foggers and thermal foggers. It will eliminate odors in homes, buildings, automobiles etc. When used with a hot fogger it will dissolve the odor producing impurities deposited by smoke. **CAUTION: HARMFUL OR FATAL IF SWALLOWED, COMBUSTIBLE, VAPOR HARMFUL. MAY CAUSE EYE AND SKIN IRRITATION.** Contains petroleum distillate. Keep away from heat or open flame. Avoid prolonged or repeated breathing of vapor, or contact with skin or eyes. If swallowed, **DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY.** For eye contact, flush eyes with clear water for 15 minutes or until irritation subsides. For skin contact, remove any contaminated clothing and wash skin with soap and water. For inhalation, move to fresh air.

 Knapp Manufacturing
Fresno, CA 93727
877-278-6630
www.KnappProducts.com

KNAPP PRODUCTS