

LINE  **ONE**

FLOOR SEALER



CAUTION: KEEP OUT OF REACH OF CHILDREN.

Net Contents: 1 Gallon

KNAPP PRODUCTS

Knapp Manufacturing Fresno, CA 93727
877-278-6630 www.KnappProducts.com

Floor Sealer

Floor Sealer is an acrylic, water emulsion seal for use on asphalt tile, linoleum, concrete, vinyl, rubber, tile, terrazzo or any other flooring surface not harmed by water. Floor Sealer is naturally tough and durable and will actually increase the performance and extend the life of floor waxes and finishes. Floor Sealer will serve as an excellent foundation for all acrylic floor finishes.

DIRECTIONS AND APPLICATIONS To prepare floors for initial applications of AFP, remove all dirt and wax. (The use of a floor machine and scrubbing or stripping pad will save labor.) After scrubbing or stripping, rinse the floor thoroughly with clean water to ensure the greatest gloss, slip resistance and maximum wear. To insure an alkali-free floor, add 4 oz. vinegar to rinse water and mop entire floor. Apply Floor Sealer to clean, dry floor in thin, even coats, using either a lambswool wax applicator or clean rayon blend mop. Avoid puddling. A second coat may be required on very porous surfaces. AFP is dry to touch in 30 min. but at least one hour should be allowed between coats. Note: Protect from freezing. Do not take internally.

First Aid Avoid contact with eyes. For eye contact, flush with water repeatedly. If ingested, give two glasses of water, induce vomiting and get immediate medical attention. Please refer to the Material Safety Data Sheet for detailed safety information and procedures. In case of emergency call 1-800-255-3924.

Only for Sale to, Use and Storage by Servicepersons.