

LINE ONE

P F F

Polyurethane Fortified Finish



CAUTION: KEEP OUT OF REACH OF CHILDREN.

Net Contents: 1 Gallon

KNAPP PRODUCTS

Knapp Manufacturing Fresno, CA 93727
877-278-6630 www.KnappProducts.com

P F F

P F F is the finest choice for heavy wear or difficult to maintain floors due to high foot traffic, equipment wheels, and frequent furniture moving. By uniting high quality urethane to a premium acrylic, P F F offers exceptional wear resistance coupled with superior gloss.

DIRECTIONS FOR USE: Before applying P F F, the floor must be thoroughly cleaned and rinsed. All previous floor finish or wax should be completely removed using QFS. Pick up the stripper solution, and then allow the floor to completely dry. Apply P F F to clean, dry floor using a rayon mop or a lambswool applicator. Spread evenly over the enter floor area. Avoid excessive agitation, and do not allow product to dry in puddles. After the floor is dry, you may apply the next coat. When P F F is dry, the floor will have a high gloss and be ready for traffic.

First Aid: Avoid contact with eyes. For eye contact, flush with water. If accidentally swallowed, give two glasses of water, and contact a physician immediately. Please refer to the Material Safety Data Sheet for detailed safety information and procedures. In case of an emergency call 1-800-255-3924.

Only for Sale to, Use and Storage by Servicepersons.